



2PM30J24M3 2PM Connector Shell Size 30 24 Pin Flange Male Socket, Sealed Type, Threaded & Non-Threaded Back End

Part Number:

2PM30J24M3



Compatible Part Numbers

English P/N	2RMGD30B24Sh5E2
RENHOTECH P/N	2PM30J24M3

Basic Information

Connector Type	Panel socket
Orientation	Straight
Gender	Male
Shell Size	2PM 30
Number of Positions	24 Pin
Contact Termination	Solder
Fastening Type	Threaded

Mechanical Specification

Durability	500
------------	-----

Material Specification

Shell Material	Stainless steel
Contact Material	Copper with nickel-plated
Insulation Material	Glass sintered


Electrical Specification

Rated Current	5-30A
Rated Voltage	≤700V

Environmental Specification

Operating Temperature	-60°C - +200°C
-----------------------	----------------

Contact Layout



How to Order

2PM

22

K(J)

4

Z/M/C
Q/W

A/B

1/2/3

Series

Shell Size: 2PM14/18 22/24/27/30/33/36/39/42/45

K: Female J: Male

Number of Contacts

Z: Non-sealed standard flange receptacle
M: Sealed flange receptacle
C: Sealed bulkhead receptacle
Q: Straight cable plug
W: Angled cable plug

A: Shielded tail attachment, B: Unshielded tail attachment

1: Gold plated pin, 2: Silver plated pin, 3: Nickel plated pins

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.