




12 V / 24 V 11 Position Automotive Housing for Female Terminals Cable-to-Cable / Wire-to-Wire Gray Wire & Cable Power Hybrid

Part Number:

TE-2377860-2



Basic Information

| | |
|--------------------------------------|--|
| Number of Positions | 11 |
| Contact Size | .4mm 1.2mm |
| Series | AMP |
| Tcpn | 2377860-2 |
| Product Description | 11 POS, HYBRID, REC HSG ASSY, UNSLD, COD B |
| Mixed & Hybrid Connector | Yes |
| Connector System | Cable-to-Cable Wire-to-Wire |
| Number of Rows | 4 |
| Keying Code | B |
| Contact Type | Receptacle |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Primary Locking Feature | Integrated in Housing |
| Connector & Housing Type | Housing for Female Terminals |
| Connector Position Assurance Capable | No |
| Connector Shape | Rectangular |
| Primary Product Color | Gray |
| Mating Alignment | With |
| Mating Alignment Type | Keyed |

Mechanical Specification

| | |
|---------------------|--------------------|
| Mating Pin Diameter | .4 mm (.016 in) |
| Mating Tab Width | 1.2 mm (.047 in) |

Electrical Specification

| | |
|-----------------------------------|--------------|
| Connector & Contact Terminates To | Wire & Cable |
| Circuit Application | Power |
| Operating Voltage (VDC) | 24.0 |
| Nominal Voltage Architecture (V) | 12 24 |

Environmental Specification

| | |
|-----------------------------|-------------------------------|
| Sealable | No |
| Packaging Quantity | 600.0 |
| Operating Temperature (Max) | 105 °C (221 °F) |
| Operating Temperature Range | -40 – 105 °C (-40 – 221 °F) |
| Packaging Method | Carton |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.