



12 V / 24 V 11 Position Automotive Housing for Female Terminals Cable-to-Cable / Wire-to-Wire Blue Wire & Cable Power Hybrid

Part Number:

TE-2377860-4



Basic Information

Number of Positions	11
Contact Size	.4mm 1.2mm
Series	AMP
Tcpn	2377860-4
Product Description	11 POS, HYBRID, REC HSG ASSY, UNSLD, COD D
Mixed & Hybrid Connector	Yes
Connector System	Cable-to-Cable Wire-to-Wire
Number of Rows	4
Keying Code	D
Contact Type	Receptacle
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	Integrated in Housing
Connector & Housing Type	Housing for Female Terminals
Connector Position Assurance Capable	No
Connector Shape	Rectangular
Primary Product Color	Blue
Mating Alignment	With
Mating Alignment Type	Keyed

Mechanical Specification

Mating Pin Diameter	.4 mm (.016 in)
Mating Tab Width	1.2 mm (.047 in)

Electrical Specification

Connector & Contact Terminates To	Wire & Cable
Circuit Application	Power
Operating Voltage (VDC)	24.0
Nominal Voltage Architecture (V)	12 24

Environmental Specification

Sealable	No
Packaging Quantity	600.0
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)
Packaging Method	Carton

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.