



12 V / 24 V 11 Position Automotive Housing for Male Terminals Wire-to-Wire 4 mm (.157 in) Centerline Gray Wire & Cable Hybrid

Part Number:

TE-2377861-2



Basic Information

Number of Positions	11
Contact Size	.4mm 1.2mm
Series	AMP
Tcpn	2377861-2
Product Description	11 POS, HYBRID, TAB HSG ASSY, UNSLD, COD B
Mixed & Hybrid Connector	Yes
Connector System	Wire-to-Wire
Number of Rows	4
Keying Code	B
Contact Type	Tab
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	Locking Lance
Connector & Housing Type	Housing for Male Terminals
Connector Position Assurance Capable	No
Connector Shape	Rectangular
Primary Product Color	Gray
Mating Alignment	With
Mating Alignment Type	Keyed

Mechanical Specification

Mating Pin Diameter	.4 mm (.015 in)
Centerline (Pitch)	4 mm (.157 in)
Mating Tab Width	1.2 mm (.047 in)

Electrical Specification

Connector & Contact Terminates To	Wire & Cable
Circuit Application	Power, Signal & High Speed Data
Nominal Voltage Architecture (V)	12 24

Environmental Specification

Sealable	No
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.