



H-MTD Quad Jack to Jack Automotive Ethernet Cable - RHT-605-20856

Part Number:

RHT-605-20856



basic_information

1st Contact Type	Female Pin
2nd Contact Type	Female Pin
1st Connector	E6K10D-1CAZ5-Z
2nd Connector	E6K10D-1CAZ5-Z
1st Connector Orientation	Straight
2nd Connector Orientation	Straight
Cable Type	GG 2Speed 251
Length	Customized

electrical_specification

Impedance	100Ω
Frequency Range	DC ~ 10 GHz

environmental_specification

Temperature Range	-40°C to +105°C
-------------------	-----------------

1	2	3	4	5	6																																																						
			<table border="1"> <tr> <td>发行版本 Revision</td> <td>修改内容 Description</td> <td>制图 Drawing</td> <td>日期 Date</td> </tr> <tr> <td>A</td> <td>First release</td> <td>Riky</td> <td>2025.03.29</td> </tr> </table>		发行版本 Revision	修改内容 Description	制图 Drawing	日期 Date	A	First release	Riky	2025.03.29																																															
发行版本 Revision	修改内容 Description	制图 Drawing	日期 Date																																																								
A	First release	Riky	2025.03.29																																																								
Connector 1: Rosenberger : E6K10D-1CAZ5-Z Connector 2: Rosenberger : E6K10D-1CAZ5-Z																																																											
<table border="1"> <tr> <td colspan="2">1.Electrical:</td> <td colspan="2">100 OHM NOMINAL</td> </tr> <tr> <td>A.Impedance</td> <td></td> <td colspan="2">DC-10CHZ</td> </tr> <tr> <td>B.Frequency Range</td> <td></td> <td colspan="2">500 VRMS MIN</td> </tr> <tr> <td>C.Hi-Pot</td> <td></td> <td colspan="2">100% TEST</td> </tr> <tr> <td>D.Continuity</td> <td></td> <td colspan="2"></td> </tr> <tr> <td colspan="2">2.Mechanical:</td> <td colspan="2">110N MIN.</td> </tr> <tr> <td>A.Cable Retention</td> <td></td> <td colspan="2">-40°C TO 105°C</td> </tr> <tr> <td>B.Temperature Range</td> <td></td> <td colspan="2"></td> </tr> </table>						1.Electrical:		100 OHM NOMINAL		A.Impedance		DC-10CHZ		B.Frequency Range		500 VRMS MIN		C.Hi-Pot		100% TEST		D.Continuity				2.Mechanical:		110N MIN.		A.Cable Retention		-40°C TO 105°C		B.Temperature Range																									
1.Electrical:		100 OHM NOMINAL																																																									
A.Impedance		DC-10CHZ																																																									
B.Frequency Range		500 VRMS MIN																																																									
C.Hi-Pot		100% TEST																																																									
D.Continuity																																																											
2.Mechanical:		110N MIN.																																																									
A.Cable Retention		-40°C TO 105°C																																																									
B.Temperature Range																																																											
<table border="1"> <tr> <td colspan="2">客户料号 Cus/P/N</td> <td colspan="2">料 号 P/N</td> <td colspan="2">品 名 Name</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">RHT-605-20856</td> <td colspan="2">H-MTD Code Z Quad Jack Automotive Ethernet Cable</td> </tr> <tr> <td colspan="2">未注公差 Unless Otherwise Specified</td> <td>单位 Unit</td> <td>mm</td> <td>版本 Revision</td> <td>A</td> </tr> <tr> <td colspan="2">线性 Linear</td> <td>比例 Scale</td> <td>--</td> <td colspan="2">图 纸 确 认 DRAWING CHECKED</td> </tr> <tr> <td colspan="2">角度 Angles</td> <td>页 码 Page</td> <td>1/1</td> <td colspan="2">客户确认 Customer Approved</td> </tr> <tr> <td colspan="2"></td> <td colspan="2">Third Angle Projection</td> <td colspan="2">日期 Date</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2">Riky</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2">Jason</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2">2025.03.29</td> </tr> </table>						客户料号 Cus/P/N		料 号 P/N		品 名 Name				RHT-605-20856		H-MTD Code Z Quad Jack Automotive Ethernet Cable		未注公差 Unless Otherwise Specified		单位 Unit	mm	版本 Revision	A	线性 Linear		比例 Scale	--	图 纸 确 认 DRAWING CHECKED		角度 Angles		页 码 Page	1/1	客户确认 Customer Approved				Third Angle Projection		日期 Date						Riky						Jason						2025.03.29	
客户料号 Cus/P/N		料 号 P/N		品 名 Name																																																							
		RHT-605-20856		H-MTD Code Z Quad Jack Automotive Ethernet Cable																																																							
未注公差 Unless Otherwise Specified		单位 Unit	mm	版本 Revision	A																																																						
线性 Linear		比例 Scale	--	图 纸 确 认 DRAWING CHECKED																																																							
角度 Angles		页 码 Page	1/1	客户确认 Customer Approved																																																							
		Third Angle Projection		日期 Date																																																							
				Riky																																																							
				Jason																																																							
				2025.03.29																																																							
<table border="1"> <tr> <td>2</td> <td>Original ROSENBERGER H-MTD CONNECTOR E6K10D-1CAZ5-Z</td> <td>2</td> <td>SET</td> </tr> <tr> <td>1</td> <td>G&G 10G ETHERNET CABLE GG2Speed 251</td> <td>//</td> <td>MM</td> </tr> <tr> <td>ITEM</td> <td>DESCRIPTION</td> <td>QTY</td> <td>UNIT</td> </tr> </table>						2	Original ROSENBERGER H-MTD CONNECTOR E6K10D-1CAZ5-Z	2	SET	1	G&G 10G ETHERNET CABLE GG2Speed 251	//	MM	ITEM	DESCRIPTION	QTY	UNIT																																										
2	Original ROSENBERGER H-MTD CONNECTOR E6K10D-1CAZ5-Z	2	SET																																																								
1	G&G 10G ETHERNET CABLE GG2Speed 251	//	MM																																																								
ITEM	DESCRIPTION	QTY	UNIT																																																								
1	2	3	4	5	6																																																						

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.