



Dual Port H-MTD Female to Female Automotive Ethernet Cable - RHT-605-20863

Part Number:

RHT-605-20863



basic_information

1st Contact Type	Female Pin
2nd Contact Type	Female Pin
1st Connector	E6K10B-1CAZ5-Z
2nd Connector	E6K10B-1CAZ5-Z
1st Connector Orientation	Straight
2nd Connector Orientation	Straight
Cable Type	GG 2Speed 251
Length	Customized

electrical_specification

Impedance	100Ω
Frequency Range	DC ~ 10 GHz

environmental_specification

Temperature Range	-40°C to +105°C
-------------------	-----------------

1	2	3	4	5	6																																										
			<table border="1"> <tr> <td>发行版本 Revision</td> <td>修改内容 Description</td> <td>制图 Drawing</td> <td>日期 Date</td> </tr> <tr> <td>A</td> <td>First release</td> <td>Riky</td> <td>2025.03.29</td> </tr> </table>		发行版本 Revision	修改内容 Description	制图 Drawing	日期 Date	A	First release	Riky	2025.03.29																																			
发行版本 Revision	修改内容 Description	制图 Drawing	日期 Date																																												
A	First release	Riky	2025.03.29																																												
P1 L P2 Connector 1: Rosenberger : E6K10B-1CAZ5-Z Connector 2: Rosenberger : E6K10B-1CAZ5-Z																																															
<table border="1"> <tr> <td colspan="2">CONNECTOR P1</td> <td colspan="2">CONNECTOR P2</td> </tr> <tr> <td>1-1</td> <td>White</td> <td>1-1</td> <td>White</td> </tr> <tr> <td>1-2</td> <td>Green</td> <td>1-2</td> <td>Green</td> </tr> <tr> <td>2-1</td> <td>White</td> <td>2-1</td> <td>White</td> </tr> <tr> <td>2-2</td> <td>Green</td> <td>2-2</td> <td>Green</td> </tr> </table>						CONNECTOR P1		CONNECTOR P2		1-1	White	1-1	White	1-2	Green	1-2	Green	2-1	White	2-1	White	2-2	Green	2-2	Green																						
CONNECTOR P1		CONNECTOR P2																																													
1-1	White	1-1	White																																												
1-2	Green	1-2	Green																																												
2-1	White	2-1	White																																												
2-2	Green	2-2	Green																																												
<table border="1"> <tr> <td>PART NO.</td> <td>LENGTH</td> </tr> <tr> <td>RHT-605-20863-0.5M</td> <td>500±10</td> </tr> <tr> <td>RHT-605-20863-1M</td> <td>1000±15</td> </tr> </table>						PART NO.	LENGTH	RHT-605-20863-0.5M	500±10	RHT-605-20863-1M	1000±15																																				
PART NO.	LENGTH																																														
RHT-605-20863-0.5M	500±10																																														
RHT-605-20863-1M	1000±15																																														
1.Electrical: A.Impedance 100 OHM NOMINAL B.Frequency Range DC-10CHZ C.Hi-Pot 500 VRMS MIN D.Continuity 100% TEST 2.Mechanical: A.Cable Retention 110N MIN. B.Temperature Range -40°C TO 105°C																																															
<table border="1"> <tr> <td colspan="2"> 仁奥伟业 RENHOTECH </td> <td colspan="4"> RENHOTECH GROUP </td> </tr> <tr> <td>客户料号 Cus/P/N</td> <td></td> <td>料号 P/N</td> <td>RHT-605-20863</td> <td>品名 Name</td> <td>Dual Port H-MTD Vehicle Automotive Ethernet Cable Harness</td> </tr> <tr> <td>未注公差 Unless Otherwise Specified</td> <td>单位 Unit</td> <td>mm</td> <td>版本 Revision</td> <td>A</td> <td>图纸确认 DRAWING APPROVAL</td> </tr> <tr> <td>线性 Linear</td> <td>0.5-6 ±0.2 >6-30 ±0.3 >30 ±2%</td> <td>比例 Scale</td> <td>1:1</td> <td>审核 Checked</td> <td>Riky</td> </tr> <tr> <td>角度 Angles</td> <td>±3°</td> <td>页码 Page</td> <td>1/1</td> <td>客户确认 Customer Approved</td> <td>Jason</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"> Third Angle Projection </td> <td>日期 Date</td> </tr> <tr> <td colspan="3"></td> <td colspan="2"></td> <td>2025.03.29</td> </tr> </table>						仁奥伟业 RENHOTECH		RENHOTECH GROUP				客户料号 Cus/P/N		料号 P/N	RHT-605-20863	品名 Name	Dual Port H-MTD Vehicle Automotive Ethernet Cable Harness	未注公差 Unless Otherwise Specified	单位 Unit	mm	版本 Revision	A	图纸确认 DRAWING APPROVAL	线性 Linear	0.5-6 ±0.2 >6-30 ±0.3 >30 ±2%	比例 Scale	1:1	审核 Checked	Riky	角度 Angles	±3°	页码 Page	1/1	客户确认 Customer Approved	Jason				Third Angle Projection		日期 Date						2025.03.29
仁奥伟业 RENHOTECH		RENHOTECH GROUP																																													
客户料号 Cus/P/N		料号 P/N	RHT-605-20863	品名 Name	Dual Port H-MTD Vehicle Automotive Ethernet Cable Harness																																										
未注公差 Unless Otherwise Specified	单位 Unit	mm	版本 Revision	A	图纸确认 DRAWING APPROVAL																																										
线性 Linear	0.5-6 ±0.2 >6-30 ±0.3 >30 ±2%	比例 Scale	1:1	审核 Checked	Riky																																										
角度 Angles	±3°	页码 Page	1/1	客户确认 Customer Approved	Jason																																										
			Third Angle Projection		日期 Date																																										
					2025.03.29																																										
<table border="1"> <tr> <td>2</td> <td>Original ROSENBERGER H-MTD CONNECTOR E6K10B-1CAZ5-Z</td> <td>2</td> <td>SET</td> </tr> <tr> <td>1</td> <td>G&G 10G ETHERNET CABLE GG2Speed 251</td> <td>//</td> <td>MM</td> </tr> <tr> <td>ITEM</td> <td>DESCRIPTION</td> <td>QTY</td> <td>UNIT</td> </tr> </table>						2	Original ROSENBERGER H-MTD CONNECTOR E6K10B-1CAZ5-Z	2	SET	1	G&G 10G ETHERNET CABLE GG2Speed 251	//	MM	ITEM	DESCRIPTION	QTY	UNIT																														
2	Original ROSENBERGER H-MTD CONNECTOR E6K10B-1CAZ5-Z	2	SET																																												
1	G&G 10G ETHERNET CABLE GG2Speed 251	//	MM																																												
ITEM	DESCRIPTION	QTY	UNIT																																												
1	2	3	4	5	6																																										

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.