



Automotive Ethernet Cable IX A Key to H-MTD - RHT-605-20938

Part Number:

RHT-605-20938



basic_information

1st Connector	IX40G-A-10S-CV (7.0)
2nd Connector	E6K10A-1CAZ5-Z
1st Connector Orientation	Straight
2nd Connector Orientation	Straight
Cable Type	GG 2Speed 251
Length	Customized

electrical_specification

Impedance	100 Ω
Frequency Range	DC ~ 10 GHz

environmental_specification

Temperature Range	-40°C to +105°C
-------------------	-----------------

1	2	3	4	5	6
A		B		C	
B		C		D	
C		D		E	
D		E		F	
E		F		G	
F		G		H	
G		H		I	
H		I		J	
I		J		K	
J		K		L	
K		L		M	
L		M		N	
M		N		O	
N		O		P	
O		P		Q	
P		Q		R	
Q		R		S	
R		S		T	
S		T		U	
T		U		V	
U		V		W	
V		W		X	
W		X		Y	
X		Y		Z	
Y		Z		AA	
Z		AA		AB	
AA		AB		AC	
AB		AC		AD	
AC		AD		AE	
AD		AE		AF	
AE		AF		AG	
AF		AG		AH	
AG		AH		AI	
AH		AI		AJ	
AI		AJ		AK	
AJ		AK		AL	
AK		AL		AM	
AL		AM		AN	
AM		AN		AO	
AN		AO		AP	
AO		AP		AQ	
AP		AQ		AR	
AQ		AR		AS	
AR		AS		AT	
AS		AT		AU	
AT		AU		AV	
AU		AV		AW	
AV		AW		AX	
AW		AX		AY	
AX		AY		AZ	
AY		AZ		BA	
AZ		BA		BB	
BA		BB		BC	
BB		BC		BD	
BC		BD		BE	
BD		BE		BF	
BE		BF		BG	
BF		BG		BH	
BG		BH		BI	
BH		BI		BJ	
BI		BJ		BK	
BJ		BK		BL	
BK		BL		BM	
BL		BM		BN	
BM		BN		BO	
BN		BO		BP	
BO		BP		BQ	
BP		BQ		BR	
BQ		BR		BS	
BR		BS		BT	
BS		BT		BU	
BT		BU		BV	
BU		BV		BW	
BV		BW		BX	
BW		BX		BY	
BX		BY		BZ	
BY		BZ		CA	
BZ		CA		CB	
CA		CB		CC	
CB		CC		CD	
CC		CD		CE	
CD		CE		CF	
CE		CF		CG	
CF		CG		CH	
CG		CH		CI	
CH		CI		CJ	
CI		CJ		CK	
CJ		CK		CL	
CK		CL		CM	
CL		CM		CN	
CM		CN		CO	
CN		CO		CP	
CO		CP		CQ	
CP		CQ		CR	
CQ		CR		CS	
CR		CS		CT	
CS		CT		CU	
CT		CU		CV	
CU		CV		CW	
CV		CW		CX	
CW		CX		CY	
CX		CY		CZ	
CY		CZ		DA	
CZ		DA		DB	
DA		DB		DC	
DB		DC			

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.