



Cable-to-Board Horizontal 12 Position Board Mount Z
 Code 2 mm (.08 in) Centerline -40 – 105 °C (-40 – 221 °F)
 Data Connectivity Headers

Part Number:

RHT-1-2397129-4

Basic Information

Tcpn	1-2397129-4
Product Description	GEMnet HDR, ASSY, 6P, 90deg,COD Z
Mixed & Hybrid Connector	No
Connector System	Cable-to-Board
Number of Rows	2
PCB Mount Orientation	Horizontal
Number of Positions	12
Keying Code	Z
Contact Type	Pin
Center Contact	With
Connector Mounting Type	Board Mount

Electrical Specification

Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	2
Termination Method to PCB	Through Hole - Solder
Mating Retention	With
PCB Mount Retention	With

Environmental Specification

Sealable	No
Shielded	No
Packaging Quantity	65.0
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)
Packaging Method	Reel

Material Specification

Contact Mating Plating	Gold (Au)
Housing Color	Pastel Orange
Dielectric Material	Liquid Crystal Polymer (LCP)

Mechanical Specification

Mating Pin Diameter	.5 mm (.02 in)
Centerline (Pitch)	2 mm (.08 in)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.