


Cable-to-Board Shielded Horizontal 2 Position Board Mount E Code 4 mm (.15 in) Centerline Signal Data Connectivity Headers

Part Number:

**RHT-2306368-5**



### Basic Information

Tcpn	2306368-5
Product Description	2P,MATE-AX,HDR ASSY,90DEG.COD E
Connector System	Cable-to-Board
Number of Rows	1
PCB Mount Orientation	Horizontal
Number of Positions	2
Keying Code	E
Contact Type	Pin
Connector Mounting Type	Board Mount

### Electrical Specification

Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	3
Termination Method to PCB	Through Hole - Solder
Circuit Application	Signal

### Environmental Specification

Sealable	No
Shielded	Yes
Packaging Quantity	370.0
Operating Temperature (Max)	105 °C ( 221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)
Packaging Method	Reel

### Material Specification

Contact Mating Plating	Silver (Ag)
Housing Color	May Green
UL Flammability Rating	UL 94HB
Outer Contact Plating	Tin (Sn)

### Mechanical Specification

Mating Pin Diameter	.4 mm (.016 in)
Centerline (Pitch)	4 mm (.15 in)

#### Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.