



Cable-to-Board 180° Cable Exit 4 Position C Code Housing for Female Terminals 4 mm (.157 in) Centerline Crimp Data Connectivity Housings

Part Number:

RHT-2348802-3



Basic Information	
Tcpn	2348802-3
Product Description	4,COAX,SOC HSG ASSY,UNSLD,180DEG
Mixed & Hybrid Connector	No
Connector System	Cable-to-Board
Number of Rows	2
Number of Positions	4
Keying Code	C
Contact Type	Receptacle
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	On the Terminal
Connector & Housing Type	Housing for Female Terminals
Connector Position Assurance Capable	No

Electrical Specification

Connector & Contact Terminates To	Wire & Cable
Contact Current Rating (Max) (A)	1
Circuit Application	Signal
Impedance (Ω)	50.0
Termination to Cable	Crimp
Cable Type	Coaxial

Environmental Specification

Sealable	No
Shielded	No
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)

Material Specification

Contact Mating Plating	Gold (Au)
Connector Center Contact Plating	Gold (Au)
Housing Color	Light Blue

Mechanical Specification

Mating Pin Diameter	.4 mm (.016 in)
Centerline (Pitch)	4 mm (.157 in)
Cable Exit Angle	180°

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.