



Cable-to-Cable 180° Cable Exit 4 Position C Code Housing for Male Terminals 4 mm (.157 in) Centerline Crimp Signal Data Connectivity Housings

Part Number:

RHT-2362803-3



Basic Information

| | |
|--------------------------------------|--|
| Tcpn | 2362803-3 |
| Product Description | 4P,MATE-AX,PIN HSG ASSY,COD C,11MMCLIP |
| Connector System | Cable-to-Cable |
| Number of Rows | 2 |
| Number of Positions | 4 |
| Keying Code | C |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Primary Locking Feature | On the Terminal |
| Connector & Housing Type | Housing for Male Terminals |
| Connector Position Assurance Capable | No |

Electrical Specification

| | |
|-----------------------------------|--------------|
| Connector & Contact Terminates To | Wire & Cable |
| Circuit Application | Signal |
| Termination to Cable | Crimp |
| Cable Type | RTK 031 |

Environmental Specification

| | |
|-----------------------------|-------------------------------|
| Sealable | No |
| Shielded | No |
| Operating Temperature (Max) | 105 °C (221 °F) |
| Operating Temperature Range | -40 – 105 °C (-40 – 221 °F) |

Material Specification

| | |
|---------------|------------|
| Housing Color | Light Blue |
|---------------|------------|

Mechanical Specification

| | |
|---------------------|-------------------|
| Mating Pin Diameter | .4 mm (.015 in) |
| Centerline (Pitch) | 4 mm (.157 in) |
| Cable Exit Angle | 180° |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.