




Cable-to-Board Horizontal 1 Position Board Mount A  
 Code Signal -40 - 105 °C (-40 - 221 °F) Data  
 Connectivity Headers

Part Number:

**RHT-2371229-1**



### Basic Information

Tcpn	2371229-1
Product Description	1POS,COAX,HDR ASSY,90DEG,COD A
Connector System	Cable-to-Board
Number of Rows	1
PCB Mount Orientation	Horizontal
Number of Positions	1
Keying Code	A
Connector Mounting Type	Board Mount

### Electrical Specification

Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	1
Termination Method to PCB	Through Hole - Solder
Circuit Application	Signal

**Environmental Specification**

Sealable	No
Shielded	No
Operating Temperature (Max)	105 °C ( 221 °F )
Operating Temperature Range	-40 – 105 °C ( -40 – 221 °F )

**Material Specification**

Contact Mating Plating	Gold (Au)
Housing Color	Black
UL Flammability Rating	UL 94HB

**Mechanical Specification**

Mating Pin Diameter	.4 mm ( .01 in )
---------------------	------------------

**Disclaimer**

---

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.