



Wire-to-Board Horizontal 2 Position Board Mount B
Code 2 mm (.07 in) Centerline Signal -40 – 105 °C (-40 – 221 °F) Data Connectivity Headers

Part Number:

RHT-2374901-2



Basic Information

Tcpn	2374901-2
Product Description	GEMnet HDR, ASSY, 1P, 90deg,COD B
Mixed & Hybrid Connector	No
Connector System	Wire-to-Board
Number of Rows	1
PCB Mount Orientation	Horizontal
Number of Positions	2
Keying Code	B
Contact Type	Pin
Center Contact	With
Connector Mounting Type	Board Mount

Electrical Specification

Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	2
Termination Method to PCB	Through Hole - Solder
Mating Retention	With
PCB Mount Retention	With
Circuit Application	Signal

Environmental Specification

Sealable	No
Shielded	No
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)

Material Specification

Contact Mating Plating	Gold (Au)
Housing Color	White
Dielectric Material	Liquid Crystal Polymer (LCP)

Mechanical Specification

Mating Pin Diameter	.5 mm (.02 in)
Centerline (Pitch)	2 mm (.07 in)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.