





Wire-to-Board Sealable Shielded Horizontal 16 Position Board Mount A Code 5 mm (.19 in) Centerline Signal Data Connectivity Headers

Part Number:

RHT-2401856-1



Basic Information

Tcprn	2401856-1
Product Description	4X4 COMBO,MATE-AX,HDR ASSY,90DEG,SEALED
Connector System	Wire-to-Board
Number of Rows	2
PCB Mount Orientation	Horizontal
Number of Positions	16
Keying Code	A
Connector Mounting Type	Board Mount

Electrical Specification

Connector & Contact Terminates To	Printed Circuit Board
Termination Method to PCB	Through Hole - Solder
Circuit Application	Signal

Environmental Specification

Sealable	Yes
Shielded	Yes
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 - 105 °C (-40 - 221 °F)

Material Specification

Contact Mating Plating	Gold (Au)
Housing Color	Water Blue
UL Flammability Rating	UL 94HB

Mechanical Specification

Mating Pin Diameter	.4 mm (.01 in)
Centerline (Pitch)	5 mm (.19 in)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.