



Cable-to-Board / Wire-to-Board 180° Cable Exit 4 Position Housing for Female Terminals 4 mm (.15 in) Centerline Crimp Data Connectivity Housings

Part Number:

RHT-2407884-1



Basic Information

Tcprn	2407884-1
Product Description	MATE-AX,NET PLUG HSG
Mixed & Hybrid Connector	Yes
Connector System	Cable-to-Board Wire-to-Board
Number of Rows	2
Number of Positions	4
Contact Type	Socket
Center Contact	Without
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	On the Terminal
Connector & Housing Type	Housing for Female Terminals
Snap-Lock	Without

Electrical Specification

Connector & Contact Terminates To	Wire & Cable
Termination to Cable	Crimp
Nominal Voltage Architecture (V)	60.0

Environmental Specification

Sealable	No
Shielded	No
Packaging Quantity	1.0
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)
Packaging Method	Bag

Material Specification

Housing Color	Black
Body Material	PBT GF10
Ferrule	With

Mechanical Specification

Mating Pin Diameter	.4 mm (.01 in)
Centerline (Pitch)	4 mm (.15 in)
Connector Height	10.2 mm (.4 in)
Product Length	28.3 mm (1.11 in)
Product Width	23 mm (.9 in)
Mating Tab Width	.5 mm (.02 in)
Mating Tab Thickness	.4 mm (.01 in)
Cable Exit Type	Straight
Cable Exit Angle	180°

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.