

BNC Connector 1x4 R/A Jack PCB Mount Through Hole 50 Ohm - RHT-610-0011



Drawing

				<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>REV</th> <th>DESCRIPTION</th> <th>DWN</th> <th>DATE</th> <th>APPROVEN</th> </tr> <tr> <td>A</td> <td>First issue</td> <td>Mr. Wang</td> <td>2016/3/02</td> <td>John kine</td> </tr> </table>		REV	DESCRIPTION	DWN	DATE	APPROVEN	A	First issue	Mr. Wang	2016/3/02	John kine																																			
REV	DESCRIPTION	DWN	DATE	APPROVEN																																														
A	First issue	Mr. Wang	2016/3/02	John kine																																														
<p>Specifications Impedance:50 Ohms Frequency Range:DC~3G VSWR:1.3MAX Working Voltage:500V rms @ sea level Insulation Resistance:5000 Ohms min Temperature Range:-55°C TO +155°C Relative Temperature:≤95%(40° C±2° C) Drawings products are in line with ROHS standards</p>																																																		
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>NO</th> <th>DESCRIPTION</th> <th>MATERIAL</th> <th>FINISH</th> <th>QTY</th> </tr> <tr> <td>6</td> <td>Insulator</td> <td>POM</td> <td>-----</td> <td>4</td> </tr> <tr> <td>5</td> <td>Solder column</td> <td>Iron</td> <td>NICKEL</td> <td>4</td> </tr> <tr> <td>4</td> <td>IRON PLATES</td> <td>Iron</td> <td>NICKEL</td> <td>1</td> </tr> <tr> <td>3</td> <td>PANEL</td> <td>ABS</td> <td>BLACK</td> <td>1</td> </tr> <tr> <td>2</td> <td>PIN</td> <td>BRASS</td> <td>NICKEL</td> <td>4</td> </tr> <tr> <td>1</td> <td>BODY</td> <td>ZINC</td> <td>NICKEL</td> <td>4</td> </tr> </table>		NO	DESCRIPTION	MATERIAL	FINISH	QTY	6	Insulator	POM	-----	4	5	Solder column	Iron	NICKEL	4	4	IRON PLATES	Iron	NICKEL	1	3	PANEL	ABS	BLACK	1	2	PIN	BRASS	NICKEL	4	1	BODY	ZINC	NICKEL	4	<p>NOTE:</p> <p>DRAWN: Zelin. Zhang 2016/03/02 CHECKED: [Signature] APPROVALS: John Kine 09.03.2016</p>		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>Tolerance</td> <td>0-6 ±0.10 6-30 ±0.20 30-120 ±0.30 Angular ±2°</td> </tr> <tr> <td>View</td> <td></td> </tr> <tr> <td>UNIT</td> <td>MM</td> </tr> <tr> <td>SCALE</td> <td>1:1</td> </tr> </table>		Tolerance	0-6 ±0.10 6-30 ±0.20 30-120 ±0.30 Angular ±2°	View		UNIT	MM	SCALE	1:1	<p>RENHOTEC GROUP www.renhotec.com</p> <p>Name: BNC 1X4 CONNECTOR DGN SIZE A Product NO. RENHOTEC-610-0011 REV [] Date/Time 2016/3/02 CAD FILE D/company drawings/BD SHEET: 1 OF 1</p>	
NO	DESCRIPTION	MATERIAL	FINISH	QTY																																														
6	Insulator	POM	-----	4																																														
5	Solder column	Iron	NICKEL	4																																														
4	IRON PLATES	Iron	NICKEL	1																																														
3	PANEL	ABS	BLACK	1																																														
2	PIN	BRASS	NICKEL	4																																														
1	BODY	ZINC	NICKEL	4																																														
Tolerance	0-6 ±0.10 6-30 ±0.20 30-120 ±0.30 Angular ±2°																																																	
View																																																		
UNIT	MM																																																	
SCALE	1:1																																																	

Basic Information

Connector Type	Jack
Contact Type	Female Pin
Fastening Type	Bayonet
Mounting Feature	Through Hole
Mounting Type	PCB Mount
Number of Ports	4
Orientation	Right Angle
RF Series	BNC Type

Electrical Specification

Dielectric Withstanding Voltage	1500 V rms
Frequency Range	0-4 GHz for 50 ohm
Impedance	50 ohm

Environmental Specification

Temperature Range	POM -40°C ~+60°C, Teflon -55°C ~+155°C
-------------------	--

Mechanical Specification

Mating Durability	≥ 500 Cycles
-------------------	--------------

Material and Finish

Component Description	Material	Finish
Shell	Zinc Alloy	Nickel Plated
Insulator	Teflon White	
Center Contact	Copper Alloy	Tin Plated

Impedance Testing

Impedance	50 ohm
-----------	--------

Frequency & VSWR Test Report

Frequency Range	0-4 GHz for 50 ohm
VSWR	R/A type $\leq 1.30/3\text{GHz}$, Straight type $\leq 1.22/3\text{GHz}$



Contact Resistance Test

Contact Type	Female Pin
Center Contact Resistance	$\leq 1.5 \text{ M}\Omega$ (Milliohms Max.)
Outer Contact Resistance	$\leq 2.0 \text{ M}\Omega$ (Milliohms Max.)



Working Voltage & Insulation Resistance Test

Working Voltage	500 V rms
Insulation Resistance	$\geq 5 \times 10^3 M\Omega$ (Megohms MIN.)



Version History

REV	Date	Revise Contents	Drafter	Approver
A.0	2026.3.23	The initial formulation	Marcella	Joson

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.