



Impedance: 50 Ohms
Frequency Range: 0~6GHz
VSWR: 1.25max
Working Voltage: <170 V rms @ sea level
Insulation Resistance: 5000 Ohms min
Temperature Range: -65°C TO +165°C
Drawings products are in line with ROHS standards

1	Body	Brass	GOLD	1	NOTE:		Tolerance	0-6 ±0.10 6-30 ±0.20 30-120 ±0.30 Angular ±2°	 RENHOTECH GROUP www.renhotec.com
2	Insulation	Teflon	White	1					
3	Pin	Copper	GOLD	1					
4									
5					DRAWN Zelin.CHEN	2016/09/03	View		Name: MCX PLUG R/A FOR RG405 CABLE
6									
7					CHECKED		UNIT	MM	SIZE A Product NO. RHT-617-0080 REV A
8									
9					APPROVALS	03/09.2016	SCALE	1:1	Date Time 2016/9/03 CAD FILE D:\company drawings\BD SHEET: 1 OF 1
10									
NO	Component Number	Material	Finish	QTY	John				

RENHOTEC
www.renhotec.com

RENHOTEC GROUP

Name:	MCX PLUG R/A FOR RG405 CABLE
-------	------------------------------

SIZE	Product NO. RHT-617-0080
------	--------------------------

DateTime	2016/9/03
----------	-----------

CAD FILE
D/company drawings/BD

SHEET: 1 OF 1