



Cable-to-Cable / Wire-to-Wire 180° Cable Exit 1 Position D Code Housing for Female Terminals Crimp High Speed Data Data Connectivity Housings

Part Number:

TE-2-2310137-4

Basic Information	
Number of Positions	T MENUTE RESPONSE MAN
Series	MATE-AX
Tcpn	2-2310137-4
Product Description	1 P MATE-AX, SOC HSG W CPA, COD D
Mixed & Hybrid Connector	No
Connector System	Cable-to-Cable   Wire-to-Wire
Number of Rows	MEDINOTES REPORTED
Keying Code	D
Contact Type	Socket
Center Contact	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	On the Terminal
Connector & Housing Type	Housing for Female Terminals
Snap-Lock	Without

Mechanical Specification				
Mating Pin Diameter	.4 mm ( .016 in )	REMOTEC	PREMINIST	EC AEN
Connector Height	10.75 mm ( .42 in )			
Product Length	8.3 mm ( .32 in )			
Product Width	18.8 mm (.74 in)			
Cable Exit Type	Straight			
Cable Exit Angle	180°			



Material Specification	
Contact Mating Plating	Silver (Ag)
Housing Color	Claret Violet
Body Material	PA66 GF30
Outer Contact Plating	Tin (Sn)
Ferrule	With

Electrical Specification	
Connector & Contact Terminates To	Wire & Cable
Mating Retention	With
Operating Voltage (VDC)	60.0
Impedance ( $\Omega$ )	50.0
Termination to Cable	Crimp
Cable Type	RG 174   RTK 031

Environmental Specification	
Sealable	No
Operating Temperature (Max)	105 °C (221 °F)

## **Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.