




Wire-to-Board Sealable 180° Cable Exit 4 Position B
Code Housing for Female Terminals 5 mm (.2 in)
Centerline Crimp Data Connectivity Housings

Part Number:
TE-2-2354439-2

Basic Information	
Number of Positions	4
Series	MATE-AX
Tcpn	2-2354439-2
Product Description	4P,MATE-AX,SOC HSG ASSY,SLD,180DEG,CPA,B
Connector System	Wire-to-Board
Number of Rows	2
Keying Code	B
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	On the Terminal
Connector & Housing Type	Housing for Female Terminals
Connector Position Assurance Capable	Yes

Mechanical Specification	
Mating Pin Diameter	.4 mm (.01 in)
Centerline (Pitch)	5 mm (.2 in)
Cable Exit Angle	180°

Material Specification	
Housing Color	Jet Black White

Electrical Specification	
Connector & Contact Terminates To	Wire & Cable
Circuit Application	Signal
Termination to Cable	Crimp
Cable Type	RG 174

Environmental Specification

Sealable	Yes
Shielded	No
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.