



Cable-to-Cable / Wire-to-Wire 180° Cable Exit 1 Position J Code Housing for Female Terminals Crimp High Speed Data Data Connectivity Housings

Part Number:

TE-2310137-9







| REMOTEC | Rea-one | |
|--------------------------|--|--|
| Basic Information | | |
| Number of Positions | 1 8 | |
| Series | MATE-AX | |
| Topn | 2310137-9 | |
| Product Description | 1 POS,MATE-AX,SOC HSG ASSY, 180DEG, COD J | |
| Mixed & Hybrid Connector | No No | |
| Connector System | Cable-to-Cable Wire-to-Wire | |
| Number of Rows | 1 | |
| Keying Code | J STATE STAT | |
| Contact Type | Socket | |
| Center Contact | With | |
| Connector Mounting Type | Cable Mount (Free-Hanging) | |
| Primary Locking Feature | On the Terminal | |
| Connector & Housing Type | Housing for Female Terminals | |
| Snap-Lock | Without | |



| Mechanical Specification | |
|--------------------------|---------------------|
| Mating Pin Diameter | .4 mm (.016 in) |
| Connector Height | 10.75 mm (.42 in) |
| Product Length | 8.3 mm (.32 in) |
| Product Width | 18.8 mm (.74 in) |
| Cable Exit Type | Straight |
| Cable Exit Angle | 180° |

| Material Specification | | |
|------------------------|-------------|--|
| Contact Mating Plating | Silver (Ag) | |
| Housing Color | Beige | |
| Body Material | PA66 GF30 | |
| Outer Contact Plating | Tin (Sn) | |
| Ferrule | With | |

| Electrical Specification | |
|-----------------------------------|------------------|
| Connector & Contact Terminates To | Wire & Cable |
| Mating Retention | With |
| Operating Voltage (VDC) | 60.0 |
| Impedance (Ω) | 50.0 |
| Termination to Cable | Crimp |
| Cable Type | RG 174 RTK 031 |

| Environmental Specification | |
|-----------------------------|-----------------|
| Sealable | No |
| Operating Temperature (Max) | 105 °C (221 °F) |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.