



Cable-to-Cable Sealable 180° Cable Exit 1 Position A Code Housing for Female Terminals Crimp Data Connectivity Housings

Part Number:

TE-2312192-1







Basic Information	
Number of Positions	1 8
Series	MATE-AX
Topn	2312192-1
Product Description	1P,MATE-AX,SOC HSG ASSY,SLD,COD A,180
Mixed & Hybrid Connector	No No.
Connector System	Cable-to-Cable
Number of Rows	1 / /
Keying Code	A STATE THE STATE
Contact Type	Socket
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	On the Terminal
Connector & Housing Type	Housing for Female Terminals
Connector Position Assurance Capable	No

Mechanical Specification			
Mating Pin Diameter	.4 mm (.016 in)	/	
Cable Exit Angle	180°		

Material Specification	
Housing Color	Jet Black



Electrical Specification		
Connector & Contact Terminates To	Wire & Cable	
Operating Voltage (VDC)	60.0	
Termination to Cable	Crimp	
Cable Type	RTK 031	
Operating Voltage (VAC)	60.0	

Environmental Specification		
Sealable	Yes	
Shielded	No	
Packaging Quantity	800.0	
Operating Temperature (Max)	105 °C (221 °F)	
Operating Temperature Range	-40 - 105 °C (-40 - 221 °F)	
Packaging Method	Bag & Box	

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.