



Wire-to-Board Shielded Vertical 10 Position Board Mount B Code 1.8 mm (.07 in) Centerline Signal Data Connectivity Headers

Part Number:

TE-2315530-2







Basic Information		
Number of Positions	10	
Series	MATEnet	
Topn	2315530-2	
Product Description	5PORT, MATENET, HDR ASSY, 180DEG, COD B	
Mixed & Hybrid Connector	No moderne	
Connector System	Wire-to-Board	
Number of Rows	1 / / /	
PCB Mount Orientation	Vertical	
Keying Code	В	
Contact Type	Pin	
Connector Mounting Type	Board Mount	
Assembly Process Feature	Board Standoff	



Mechanical Specification	
Centerline (Pitch)	1.8 mm (.07 in)
Connector Height	21.3 mm (.838 in)
Product Length	49.8 mm (1.96 in)
Product Width	15.3 mm (.602 in)
Mating Tab Width	.5 mm (.02 in)
Mating Tab Thickness	.4 mm (.01 in)
PCB Mount Retention Type	Boardlock

Material Specification	
Contact Mating Plating	Tin (Sn)
Housing Color	White
Body Material	PA
Outer Contact Plating	Tin (Sn)

Electrical Specification	
Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	3
Termination Method to PCB	Through Hole - Solder
PCB Mount Retention	With
Circuit Application	Signal
Operating Voltage (VDC)	60.0

Environmental Specification	
Sealable	No
Shielded	Yes
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.