



Cable-to-Cable Sealable 180° Cable Exit 4 Position E Code Housing for Female Terminals 5 mm (.197 in) Centerline Data Connectivity Housings

Part Number:

TE-2354439-5







| Basic Information | |
|--------------------------------------|--|
| Number of Positions | 4 Provinces |
| Series | MATE-AX |
| Tcpn | 2354439-5 |
| Product Description | 4P,MATE-AX,SOC HSG ASSY,SLD,180DEG,COD E |
| Connector System | Cable-to-Cable |
| Number of Rows | 2 |
| Keying Code | E \ / / \ / / \ / |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Primary Locking Feature | On the Terminal |
| Connector & Housing Type | Housing for Female Terminals |
| Connector Position Assurance Capable | No |

| Mechanical Specification | |
|--------------------------|--------------------|
| Mating Pin Diameter | .4 mm (.015 in) |
| Centerline (Pitch) | 5 mm (.197 in) |
| Connector Height | 23,4 mm (.92 in) |
| Product Length | 30.85 mm (1.21 in) |
| Product Width | 17.3 mm (.68 in) |
| Cable Exit Angle | 180° |



| Material Specification | |
|------------------------|-----------------------|
| Housing Color | Jet Black May Green |

| Electrical Specification | |
|-----------------------------------|------------------|
| Connector & Contact Terminates To | Wire & Cable |
| Termination to Cable | Crimp |
| Cable Type | RG 174 RTK 031 |

| Environmental Specification | |
|-----------------------------|-----------------------------|
| Sealable | Yes |
| Shielded | No |
| Operating Temperature (Max) | 105 °C (221 °F) |
| Operating Temperature Range | -40 − 105 °C (-40 − 221 °F) |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.