





## Wire-to-Board Sealable Shielded Horizontal 16 Position Board Mount A Code 5 mm (.19 in) Centerline Signal Data Connectivity Headers

Part Number:

**TE-2401856-1**



### Basic Information

|                         |                                         |
|-------------------------|-----------------------------------------|
| Number of Positions     | 16                                      |
| Series                  | MATE-AX                                 |
| Tcpn                    | 2401856-1                               |
| Product Description     | 4X4 COMBO,MATE-AX,HDR ASSY,90DEG,SEALED |
| Connector System        | Wire-to-Board                           |
| Number of Rows          | 2                                       |
| PCB Mount Orientation   | Horizontal                              |
| Keying Code             | A                                       |
| Connector Mounting Type | Board Mount                             |

### Mechanical Specification

|                     |                |
|---------------------|----------------|
| Mating Pin Diameter | .4 mm (.01 in) |
| Centerline (Pitch)  | 5 mm (.19 in)  |

### Material Specification

|                        |            |
|------------------------|------------|
| Contact Mating Plating | Gold (Au)  |
| Housing Color          | Water Blue |
| UL Flammability Rating | UL 94HB    |

### Electrical Specification

|                                   |                       |
|-----------------------------------|-----------------------|
| Connector & Contact Terminates To | Printed Circuit Board |
| Termination Method to PCB         | Through Hole - Solder |
| Circuit Application               | Signal                |

### Environmental Specification

|                             |                               |
|-----------------------------|-------------------------------|
| Sealable                    | Yes                           |
| Shielded                    | Yes                           |
| Operating Temperature (Max) | 105 °C ( 221 °F )             |
| Operating Temperature Range | -40 – 105 °C ( -40 – 221 °F ) |

### Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.