



Cable-to-Cable / Wire-to-Wire 180° Cable Exit 1 Position Z Code Housing for Female Terminals Crimp High Speed Data Data Connectivity Housings

Part Number:

TE-3-2310137-9







| Number of Positions      | 1 PRINTED THE              |            |   |
|--------------------------|----------------------------|------------|---|
| Series                   | MATE-AX                    |            |   |
| Topn                     | 3-2310137-9                |            |   |
| Product Description      | 1 P MATE-AX, SOC HSG W C   | CPÁ, COD Z |   |
| Mixed & Hybrid Connector | No                         |            |   |
| Connector System         | Cable-to-Cable   Wire-to-\ | Vire       |   |
| Number of Rows           | 1 /                        |            |   |
| Keying Code              | Z                          |            |   |
| Contact Type             | Socket                     |            |   |
| Center Contact           | With                       |            |   |
| Connector Mounting Type  | Cable Mount (Free-Hangin   | g)         |   |
| Primary Locking Feature  | On the Terminal            |            |   |
| Connector & Housing Type | Housing for Female Termina | als        |   |
| Snap-Lock                | Without                    |            | / |



| Mechanical Specification |                     |
|--------------------------|---------------------|
| Mating Pin Diameter      | .4 mm (.016 in)     |
| Connector Height         | 10.75 mm ( .42 in ) |
| Product Length           | 8.3 mm (.32 in)     |
| Product Width            | 18.8 mm (.74 in)    |
| Cable Exit Type          | Straight            |
| Cable Exit Angle         | 180°                |

| Material Specification |             |
|------------------------|-------------|
| Contact Mating Plating | Silver (Ag) |
| Housing Color          | Water Blue  |
| Body Material          | PA66 GF30   |
| Outer Contact Plating  | Tin (Sn)    |
| Ferrule                | With        |

| Electrical Specification          |                  |
|-----------------------------------|------------------|
| Connector & Contact Terminates To | Wire & Cable     |
| Mating Retention                  | With             |
| Operating Voltage (VDC)           | 60.0             |
| Impedance ( $\Omega$ )            | 50.0             |
| Termination to Cable              | Crimp            |
| Cable Type                        | RG 174   RTK 031 |

| Environmental Specification |                 |
|-----------------------------|-----------------|
| Sealable                    | No              |
| Operating Temperature (Max) | 105 °C (221 °F) |

## **Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.