



Wire-to-Wire Sealable 180° Cable Exit 8 Position A Code Shielded Heavy Duty Sealed Connector Series Data Connectivity Housings

Part Number:

TE-9-2334935-1







Number of Positions	8		
Series	MATEnet		
Tcpn	9-2334935-1		
Product Description	HD MATEnet 1+6 TAB HSG	G. ASSY, GRP D	
Mixed & Hybrid Connector	Yes		
Connector System	Wire-to-Wire		
Number of Rows	2		
Keying Code	А		
Contact Type	Tab		
Center Contact	With		
Connector Mounting Type	Cable Mount (Free-Hang	ging)	
Primary Locking Feature	Locking Lance On the	Terminal	
Connector & Housing Type	Housing for Male Termina	als	



Mechanical Specification		
Centerline (Pitch) (mm)	1.8 4	
Centerline (Pitch) (in)	.071 .16	
Cable Exit Type	Straight to Angled Straight to Straight	
Cable Exit Angle	180°	
Mating Tab Width (mm)	.5 1.6	
Mating Tab Width (in)	.02 .063	
Mating Tab Thickness (mm)	.4 .6	
Mating Tab Thickness (in)	.016 .024	

Material Specification	
Contact Mating Plating	Silver (Ag)
Connector Center Contact Plating	Silver (Ag)
Housing Color	Black
Body Material	PBT GF
Outer Contact Plating	Nickel (Ni)
Ferrule	With

Electrical Specification	
Connector & Contact Terminates To	Wire & Cable
Contact Current Rating (Max) (A)	3 20
Mating Retention	With
Operating Voltage (VDC)	60.0
Termination to Cable	Crimp

Environmental Specification	
Sealable	Yes

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.