



Cable-to-Cable 180° Cable Exit 2 Position N Code Housing for Male Terminals 8 mm (.315 in) Centerline Crimp FAKRA Data Connectivity Housings

Part Number:

TE-1-1452480-4







| Basic Information | | | |
|--------------------------------------|------------------------------|------------|--|
| Number of Positions | 2.0 | | |
| Series | FAKRA | | |
| Tcpn | 1-1452480-4 | | |
| Product Description | 2POS,FAKRA II,JACK HSG,8MM P | ITCH, ASSY | |
| Mixed & Hybrid Connector | No | | |
| Connector System | Cable-to-Cable | | |
| Number of Rows | 1.0 | | |
| Keying Code | N RESERVE TO C. | | |
| Contact Type | Pin | | |
| Connector Mounting Type | Cable Mount (Free-Hanging) | / | |
| Connector & Housing Type | Housing for Male Terminals | | |
| Connector Position Assurance Capable | No | | |

| Mechanical Specification | | ~ |
|--------------------------|---------------------|------------------|
| Mating Pin Diameter | .5 mm (.02 in) | CLED RHISTREC |
| Centerline (Pitch) | 8 mm (.315 in) | |
| Connector Height | 13.9 mm (.547 in) | |
| Product Length | 26.4 mm (1.039 in) | NEAHOTEC PER |
| Product Width | 17.4 mm (.685 in) | |
| Cable Exit Angle | 180° | |



| Material Specification | |
|------------------------|--------------|
| Housing Color | Pastel Green |
| Body Material | PBT GF |

| Electrical Specification | |
|-----------------------------------|--------------|
| Connector & Contact Terminates To | Wire & Cable |
| Contact Current Rating (Max) (A) | 1.0 |
| Impedance (Ω) | 50.0 |
| Termination to Cable | Crimp |
| Cable Type | RG 174 |
| Nominal Voltage Architecture (V) | 800.0 |

| Environmental Specification | |
|----------------------------------|-----------------------------|
| Sealable | No |
| Shielded | No |
| Operating Temperature Range | -40 − 85 °C (-40 − 185 °F) |
| Operating Frequency Range (GHz) | 0 - 6 |
| Operating Temperature (Max) (°C) | 65 70 75 80 85 |
| Operating Temperature (Max) (°F) | 149 158 167 176 185 |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.