




Tab Terminal .8 mm (.031 in) Tab Width Tin (Sn) .25 mm (.009 in) Tab Thickness Unsealed Terminates To Wire & Cable FAKRA

Part Number:

TE-1-1897798-3



Basic Information

Series	FAKRA
Tcpn	1-1897798-3
Product Description	TAB SHIELD CONT-RF STRIPLINE
Primary Locking Feature	Clean Body
Compatible With Agency/Standards Products	OEM
Receptacle Style	180°
Interface Plating	Tin (Sn)

Mechanical Specification

Mating Tab Width	.8 mm (.031 in)
Mating Tab Thickness	.25 mm (.009 in)
Tab Length	22.89 mm (.9 in)

Material Specification

Wire Contact Termination Plating	Tin
Insulation Option	Uninsulated

Electrical Specification

Termination to Cable	Crimp
Contact Fabrication	Stamped & Formed
Crimp Type	IDC
Terminal Type	Tab
Product Terminates To	Wire & Cable
Terminal Transmits	0 – 24 A (Low Power)
Compatible Cable Type	Coax Cable
Typical Current Rating (A)	1.0
Compatible Insulation Diameter Range (mm)	1.5 – 1.7

Environmental Specification

Sealable	No
Packaging Quantity	2300.0
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 – 105 °C (-40 – 221 °F)
Packaging Method	Reel
Terminal Seal Type	Unsealed

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.