



Wire-to-Wire 90° Cable Exit 2 Position Z Code Housing for Female Terminals 8 mm (.31 in) Centerline Crimp FAKRA Data Connectivity Housings

Part Number:

TE-1-2112609-1







| Number of Positions      | 2.0                        |              |  |
|--------------------------|----------------------------|--------------|--|
| Series                   | FAKRA                      |              |  |
| Topn                     | 1-2112609-1                |              |  |
| Product Description      | 2POS,FAKRA II,PLUG,REC H   | SG,ASSY,CODZ |  |
| Mixed & Hybrid Connector | No                         |              |  |
| Connector System         | Wire-to-Wire               |              |  |
| Number of Rows           | 1.0                        |              |  |
| Keying Code              | Z                          |              |  |
| Contact Type             | Socket                     |              |  |
| Connector & Housing Type | Housing for Female Termina | als          |  |
| Snap-Lock                | Without                    |              |  |

| Mechanical Specification |                    |
|--------------------------|--------------------|
| Mating Pin Diameter      | .5 mm ( .02 in )   |
| Centerline (Pitch)       | 8 mm (.31 in)      |
| Connector Height         | 16.7 mm (.65 in)   |
| Product Length           | 17.8 mm (.7 in)    |
| Product Width            | 10.25 mm ( .4 in ) |
| Cable Exit Type          | Fixed              |
| Cable Exit Angle         | 90°                |



| Material Specification |            |
|------------------------|------------|
| Housing Color          | Water Blue |
| Ferrule                | Without    |

| Electrical Specification          |              |
|-----------------------------------|--------------|
| Connector & Contact Terminates To | Wire & Cable |
| Contact Current Rating (Max) (A)  | 1.0          |
| Impedance ( $\Omega$ )            | 50.0         |
| Termination to Cable              | Crimp        |
| Cable Type                        | DACAR 462    |
| Nominal Voltage Architecture (V)  | 800.0        |
| Operating Voltage (VAC)           | 800.0        |

| Environmental Specification     |                             |
|---------------------------------|-----------------------------|
| Sealable                        | No                          |
| Shielded                        | No                          |
| Operating Temperature (Max)     | 100 °C (212 °F)             |
| Operating Temperature Range     | -40 − 100 °C (-40 − 212 °F) |
| Operating Frequency Range (GHz) | 0 - 6                       |

## **Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.