



Cable-to-Cable 180° Cable Exit 1 Position I Code Housing for Female Terminals Crimp FAKRA Data Connectivity Housings

Part Number:

TE-1924792-9

Basic Information	
Number of Positions	1.0 minutes messages
Series	FAKRA
Tepn	1924792-9
Product Description	PLUG KIT, UNASSEM, 1 POS, RG174 KEY I
Mixed & Hybrid Connector	No
Connector System	Cable-to-Cable
Number of Rows	1.0 PRESENTED STATE STAT
Keying Code	
Contact Type	Socket
Center Contact	Without
Connector Mounting Type	Cable Mount (Free-Hanging)
Primary Locking Feature	On the Terminal
Connector & Housing Type	Housing for Female Terminals
Snap-Lock Snap-Lock	Without

Mechanical Specification				
Connector Height	15.07 mm ( .593 in )	nec	MENHOTEC	MEN
Product Length	26.67 mm (1.05 in)			
Product Width	11.94 mm ( .47 in )			
Cable Exit Type	Fixed			
Cable Exit Angle	180°			



Material Specification	
Contact Mating Plating	Gold (Au)
Connector Center Contact Plating	Gold (Au)
Housing Color	Beige
Body Material	PBT GF
Outer Contact Plating	Tin (Sn)
Ferrule	With

Electrical Specification	
Connector & Contact Terminates To	Wire & Cable
Mating Retention	With
Operating Voltage (VDC)	60.0
Impedance ( $\Omega$ )	50.0
Termination to Cable	Crimp
Cable Type	RG 174   RG 316

Environmental Specification	
Sealable	No
Operating Temperature Range	-40 - 100 °C (-40 - 212 °F)

## **Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.