



Cable-to-Cable 180° Cable Exit 1 Position Housing for Female Terminals Crimp Signal FAKRA Data Connectivity Housings

Part Number:

TE-2203274-1







| Basic Information | |
|--------------------------------------|---|
| Number of Positions | 1.0 |
| Series | FAKRA |
| Tepn | 2203274-1 |
| Product Description | CAVITY INSERT ASM, INLINE FEMALE, FAKRA |
| Connector System | Cable-to-Cable |
| Number of Rows | 1.0 |
| Contact Type | Socket |
| Center Contact | With WINDSTREE |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Connector & Housing Type | Housing for Female Terminals |
| Connector Position Assurance Capable | No |

| Mechanical Specification | | | |
|--------------------------|-------------------|------|--|
| Mating Pin Diameter | .48 mm (.019 in) | (ZI) | |
| Cable Exit Angle | 180° | | |



| Electrical Specification | | |
|-----------------------------------|----------------|--|
| Connector & Contact Terminates To | Wire & Cable | |
| Circuit Application | Signal | |
| Termination to Cable | Crimp | |
| Cable Type | RG 174 RG 58 | |
| Nominal Voltage Architecture (V) | 800.0 | |

| Environmental Specification | | |
|-----------------------------|-----------------------------|--|
| Sealable | No | |
| Shielded | No | |
| Packaging Quantity | 2500.0 | |
| Operating Temperature (Max) | 125 °C (257 °F) | |
| Operating Temperature Range | -40 − 125 °C (-40 − 257 °F) | |
| Packaging Method | Reel | |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.