



Cable-to-Cable Sealable 180° Cable Exit 1 Position B Code Housing for Female Terminals Crimp FAKRA Data Connectivity Housings

Part Number:

TE-2380551-2







иваните.	The state of the s
Basic Information	
Number of Positions	1.0
Series	FAKRA
Tcpn	2380551-2
Product Description	1P, FAKRA AUT SOC OUTER HSG, SLD, COD B
Mixed & Hybrid Connector	No Signature:
Connector System	Cable-to-Cable
Number of Rows	1.0
Keying Code	B SECONDARY SECONDARY
Contact Type	Socket
Center Contact	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Connector & Housing Type	Housing for Female Terminals
Snap-Lock	Without
Connector Position Assurance Capable	No
Compatible With Agency/Standards Products	SAE/USCAR-17



Mechanical Specification	
Mating Pin Diameter	.5 mm ( .02 in )
Connector Height	13.05 mm ( .51 in )
Product Length	11.55 mm ( .45 in )
Product Width	30.2 mm (1.18 in)
Cable Exit Type	Straight
Cable Exit Angle	180°

Material Specification	
Housing Color	Cream
Body Material	PBT GF10
Ferrule	Without

Electrical Specification	
Connector & Contact Terminates To	Wire & Cable
Termination to Cable	Crimp
Cable Type	Coaxial
Operating Voltage (VAC)	800.0

Environmental Specification	
Sealable	Yes
Shielded	No
Operating Temperature (Max)	125 °C (257 °F)
Operating Temperature Range	-40 − 125 °C (-40 − 257 °F)

## **Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.