



Cable-to-Cable 180° Cable Exit 1 Position D Code  
Housing for Male Terminals Crimp Cable Mount (Free-  
Hanging) FAKRA Data Connectivity Housings

Part Number:

**TE-5-1438911-4**

### Basic Information

|                                      |                                          |
|--------------------------------------|------------------------------------------|
| Number of Positions                  | 1.0                                      |
| Series                               | FAKRA                                    |
| Tcpn                                 | 5-1438911-4                              |
| Product Description                  | JACK KIT, UNASSEM, 180 Deg, RG-58, Fakra |
| Connector System                     | Cable-to-Cable                           |
| Number of Rows                       | 1.0                                      |
| Keying Code                          | D                                        |
| Connector Mounting Type              | Cable Mount (Free-Hanging)               |
| Primary Locking Feature              | On the Terminal                          |
| Connector & Housing Type             | Housing for Male Terminals               |
| Connector Position Assurance Capable | No                                       |

### Mechanical Specification

|                     |                 |
|---------------------|-----------------|
| Mating Pin Diameter | .5 mm (.02 in ) |
| Cable Exit Angle    | 180°            |

### Material Specification

|               |               |
|---------------|---------------|
| Housing Color | Claret Violet |
|---------------|---------------|

### Electrical Specification

|                                   |              |
|-----------------------------------|--------------|
| Connector & Contact Terminates To | Wire & Cable |
| Termination to Cable              | Crimp        |
| Cable Type                        | RG 58        |

## Environmental Specification

|                             |                               |
|-----------------------------|-------------------------------|
| Sealable                    | No                            |
| Shielded                    | No                            |
| Operating Temperature Range | -40 – 100 °C ( -40 – 212 °F ) |

### Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.