




Wire-to-Wire 180° Cable Exit 2 Position K Code Housing for Female Terminals Signal Cable Mount (Free-Hanging) FAKRA Data Connectivity Housings

Part Number:

TE-6-1924856-0



Basic Information

| | |
|---|---|
| Number of Positions | 2.0 |
| Series | FAKRA |
| Tcpn | 6-1924856-0 |
| Product Description | Plug HOUSING, 2 POSN, FAKRA, Key K, clp |
| Mixed & Hybrid Connector | No |
| Connector System | Wire-to-Wire |
| Number of Rows | 1.0 |
| Keying Code | K |
| Center Contact | Without |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Connector & Housing Type | Housing for Female Terminals |
| Snap-Lock | Without |
| Connector Position Assurance Capable | No |
| Compatible With Agency/Standards Products | USCAR |

Mechanical Specification

| | |
|------------------|---------------------|
| Connector Height | 16.85 mm (.66 in) |
| Product Length | 21.5 mm (.846 in) |
| Product Width | 16.9 mm (.665 in) |
| Cable Exit Type | Fixed |
| Cable Exit Angle | 180° |

Material Specification

| | |
|------------------------|----------|
| Contact Mating Plating | Unplated |
| Housing Color | Curry |
| Body Material | PBT GF |
| Ferrule | Without |

Electrical Specification

| | |
|-----------------------------------|--------------|
| Connector & Contact Terminates To | Wire & Cable |
| Circuit Application | Signal |
| Cable Type | Coaxial |

Environmental Specification

| | |
|----------------------------------|------------------------------|
| Sealable | No |
| Packaging Quantity | 3500.0 |
| Operating Temperature Range | -40 – 85 °C (-40 – 185 °F) |
| Operating Temperature (Max) (°C) | 65 70 75 80 85 |
| Operating Temperature (Max) (°F) | 149 158 167 176 185 |

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.