







Cable-to-Cable 180° Cable Exit 2 Position L Code
Housing for Female Terminals 8 mm Centerline Crimp
Signal FAKRA Data Connectivity Housings

Part Number:

TE-6-1924856-1



Basic Information

Number of Positions	2.0
Series	FAKRA
Tcpn	6-1924856-1
Product Description	PLUG HOUSING, 2 POSN, FAKRA, KEY L, CLP
Connector System	Cable-to-Cable
Number of Rows	1.0
Keying Code	L
Connector Mounting Type	Cable Mount (Free-Hanging)
Connector & Housing Type	Housing for Female Terminals
Connector Position Assurance Capable	No
Compatible With Agency/Standards Products	USCAR

Mechanical Specification

Centerline (Pitch) (mm)	8.0
Cable Exit Angle	180°

Electrical Specification

Connector & Contact Terminates To	Wire & Cable
Contact Current Rating (Max) (A)	1.0
Circuit Application	Signal
Impedance (Ω)	50.0
Termination to Cable	Crimp
Cable Type	Coaxial

Environmental Specification

Sealable	No
Packaging Quantity	1.0
Operating Temperature Range	-40 – 100 °C (-40 – 212 °F)
Packaging Method	Package
Operating Frequency Range (GHz)	0 – 6
Operating Temperature (Max) (°C)	65 70 75 80 85 90 100
Operating Temperature (Max) (°F)	212

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.