



Fakra Connector Male Twin Through Hole



### Basic Information

|                     |              |
|---------------------|--------------|
| Connector Type      | Plug         |
| Contact Type        | Male Pin     |
| Mounting Feature    | Through Hole |
| Mounting Type       | Panel Mount  |
| Number of Ports     | 2            |
| Number of Positions | 1 Pin        |
| Orientation         | Right Angle  |

### Electrical Specification

|                   |          |
|-------------------|----------|
| Impedance         | 50Ω      |
| Operating Voltage | 335V max |
| VSWR              | ≤1.5     |

### Environmental Specification

|                       |                 |
|-----------------------|-----------------|
| Operating Temperature | -40°C to +100°C |
|-----------------------|-----------------|

## How to Order

|             |   |   |   |   |  |   |   |
|-------------|---|---|---|---|--|---|---|
|             |  |  |  |  |  |  |  |
| Code        | A   | B   | C   | D   | E  | F   | G   |
| Color       | Deep Black  | Cream White   | Signal Blue   | Bordeaux Violet   | Leaf Green   | Brown   | Blue Gray   |
| Application | Radio with phantom supply   | Radio without phantom supply  | GPS telematics or navigation  | GSM Cellular Phone  | TV (UHF)   | TV (VHF)  | SDARS terrestrial   |
|             |  |  |  |  |  |  |  |
| Code        | H   | I   | K   | L   | M  | N   | Z   |
| Color       | Violet  | Beige   | Curry Yellow  | Carmine Red   | Pastel Orange  | Pastel Green  | Water Blue  |

### Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.