



Board-to-Board / Wire-to-Board Shielded Horizontal 4 Position Board Mount D Code Automotive HSD Data Connectivity Headers

Part Number:

TE-2286546-4







Basic Information		
Number of Positions	4	/ \ /
Series	HSD Replace	
Tcpn	2286546-4	
Product Description	HSD,HDR ASSY,90DEG,COD D	
Mixed & Hybrid Connector	No	
Connector System	Board-to-Board   Wire-to-Board	
Number of Rows	2	
PCB Mount Orientation	Horizontal	
Keying Code	D	
Contact Type	Pin	
Center Contact	With	
Connector Mounting Type	Board Mount	

Mechanical Specification		
Mating Pin Diameter	.6 mm ( .02 in )	CAU PREPARTIEC
Centerline (Pitch)	2 mm (.07 in)	
Connector Height	10.95 mm (.431 in)	
Product Length	12 mm (.472 in )	REMOTEC
Product Width	27.3 mm (1.074 in)	
PCB Mount Retention Type	Solder Tail	



Material Specification		
Contact Mating Plating	Gold (Au)	
Connector Center Contact Plating	Gold (Au)	
Housing Color	Bordeaux	
Body Material	PA6T/6 GF25   Zinc Alloy	
Outer Contact Plating	Tin (Sn)	
PCB Retention Plating	Tin	

Electrical Specification	
Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	2.5
Termination Method to PCB	Through Hole - Solder
Mating Retention	With
PCB Mount Retention	With
Operating Voltage (VDC)	60.0
Impedance ( $\Omega$ )	100.0

Environmental Specification	
Sealable	No
Operating Temperature (Max)	105 °C (221 °F)

## **Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.