



Wire-to-Board Shielded Vertical 6 Position Board Mount Z Code Automotive HSD Data Connectivity Headers

Part Number:

TE-2345180-9







Number of Positions	6	` _/	
Series	HSD		
Tcpn	2345180-9		
Product Description	6POS,HSD DIA 0.6,HDR A	ASSY, 180DEG, COD Z	
Connector System	Wire-to-Board		
Number of Rows	2		
PCB Mount Orientation	Vertical		
Keying Code	Z RENHESTEE		
Contact Type	Pin		
Connector Mounting Type	Board Mount		



Mechanical Specification	
Mating Pin Diameter	.6 mm (.02 in)
Connector Height	15.5 mm (.61 in)
Product Length	14.15 mm (.557 in)
Product Width	15.65 mm (.616 in)
Mating Tab Width	.63 mm (.02 in)
Mating Tab Thickness	.63 mm (.02 in)
PCB Mount Retention Type	Guide Pin
Centerline (Pitch) (mm)	2 2.54
Centerline (Pitch) (in)	.07 .1

Material Specification	
Contact Mating Plating	Gold (Au)
Housing Color	Water Blue
Body Material	PA
Outer Contact Plating	Tin (Sn)

Electrical Specification	
Connector & Contact Terminates To	Printed Circuit Board
Contact Current Rating (Max) (A)	2.5 5
Termination Method to PCB	Through Hole - Solder
Mating Retention	With
PCB Mount Retention	With
Operating Voltage (VDC)	100.0

Environmental Specification	
Sealable	No
Shielded	Yes
Operating Temperature (Max)	105 °C (221 °F)
Operating Temperature Range	-40 − 105 °C (-40 − 221 °F)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.