



NMEA 2000 4 Way Tee Connector

Part Number:

RHT-634-3402

Basic Information

Connector Type	Jack, Plug
Number of Positions	5 Pin
Fastening Type	Screw Connection
Series	NMEA 2000 Connectors
Key	A

Material Specification

Shell Material	PVC
Contact Material	Brass, Gold Plated
Insulation Material	PA66

Electrical Specification

Rated Current	4A
Rated Voltage	60V AC/DC
Contact Resistance	≤5MΩ
Insulation Resistance	≥100MΩ

Environmental Specification

Operating Temperature	-25℃~80℃
-----------------------	----------

The diagrams show the pin assignments for the front view of the connectors. The Male connector has pins 1, 2, 3, 4, and 5. The Female connector has pins 1, 2, 3, 4, and 5. The pin assignments are as follows:

Pin	Male Connector	Female Connector
1	Top Right	Top Right
2	Top Left	Top Left
3	Bottom Left	Bottom Left
4	Bottom Right	Bottom Right
5	Center	Center

[illegible]

How to Order



NMEA 2000 CONNECTORS
90 Degree Elbow Adapter NMEA
2000 Micro-C



NMEA 2000 CONNECTORS
High Current 7/8 T-type Splitter
Female to Male M12 Adapter
NMEA2000 Connectors



NMEA 2000 CONNECTORS
NMEA 2000 2 Way Tee Connector



NMEA 2000 CONNECTORS
NMEA 2000 4 Way Tee Connector



NMEA 2000 CONNECTORS
NMEA 2000 Single T-Adapter



NMEA 2000 CONNECTORS
NMEA 2000 Waterproof Mini
Change 7/8" T-Splitter

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.