



Push-Pull Self-locking K Series EBG Socket Panel Mount Solder Connector

Part Number:

EBG.CLL

Basic Information

Connector Type	Socket
Contact Termination	Solder
Contact Type	Female Pin
Contacts	10 Pin, 12 Pin, 14 Pin, 16 Pin, 18 Pin, 19 Pin, 2 Pin, 20 Pin, 22 Pin, 24 Pin, 26 Pin, 3 Pin, 30 Pin, 32 Pin, 4 Pin, 5 Pin, 6 Pin, 7 Pin, 8 Pin, 9 Pin
Orientation	Straight
Product Series	0K, 1K, 2K, 3K

Environmental Specification

Vibration Resistance	10-2000Hz.15g
Disinfection Resistance	-20 times(PSU), >100 times (PPSU), >200 times (PEEK)
Env Experiment	20 / 80 / 21
Environmental Experiment	50 / 175 / 21
Humidity Resistance	Up to 95% at 60 °C
Impact Resistance	100g 6ms
Ingress Protection	IP50
Leakage Rate	< 10 ⁻⁷ mbar. L.s ⁻¹
Corrosion Resistance	> 144h
Shielding Effect	> 80 dB at 1GHz, > 95 dB at 10MHz
Solvent Corrosion Resis	Average (PSU), Good (PPSU), Very Good (PEEK)
Temp Range	- 20 ° C\, + 100 ° C(00 to 1b), - 20 ° C\, + 80 ° C(2b to 5b)
Temperature Range Meta	-55°C ~ +250°C
Temperature Range Plastic	-55°C ~ +150°C (PSU), -55°C ~ +180°C (PPSU), -55°C ~ +250°C (PEEK)

Material Specification

Insulation Material	PPS
Shell Material	Copper Alloy

Mechanical Specification

Durability	> 5000 times
------------	--------------


Contact Layout

		Reference		Series	
		Solder contacts		Crimp contacts	
2			302	00-TT 0B-0K-0T 1B-1K-1T 2B-2K-2T 3B-3K-3T 5B-5K	
3			303	00-TT 0B-0K-0T 1B-1K-1T 2B-2K-2T 3B-3K-3T	
4			304	00-TT 0B-0K-0T 1B-1K-1T 2B-2K-2T 3B-3K-3T 4B-4K 5B-5K	
5			305	00-TT	
5			305	0B-0K-0T 1B-1K-1T 2B-2K-2T 3B-3K-3T	
6			306	0B-0K-0T 1B-1K-1T	
6			306	00-TT 2B-2K-2T 3B-3K-3T 4B-4K	
7			307	0B-0K-0T 1B-1K-1T 2B-2K-2T 3B-3K-3T 4B-4K	
8			308	1B-1K-1T	
8			308	2B-2K-2T 3B-3K-3T	
9			309	0B-0K-0T	
9			309	0B-0K-0T 3B-3K-3T	
10			310	1B-1K-1T 2B-2K-2T 3B-3K-3T 4B-4K 5B-5K	
12			312	0B-0K-0T	
12			312	XB	
12			312	2B-2K-2T 3B-3K-3T 4B-4K	
14			314	1B-1K-1T 2B-2K-2T 3B-3K-3T 5B-5K	
16			316	1B-1K-1T	
16			316	2B-2K-2T 3B-3K-3T 4B-4K 5B-5K	
18			318	2B-2K-2T 3B-3K-3T	
19			319	2B-2K-2T	
20			320	3B-3K-3T	
20			320	4B-4K 5B-5K	
22			322	XB	
22			322	3B-3K-3T	
24			324	3B-3K-3T 4B-4K	
26			326	2B-2K-2T 3B-3K-3T	
30			330	3B-3K-3T 4B-4K 5B-5K	
32			332	2B-2K-2T	
32			332	3B-3K	

Size

Reference		Dimensions (mm)							
Model	Series	A	B	F	G	H	L	M	N ¹⁾
EBG	3K	29	23	3	3.4	23	36.2	6.0	32.6
EBG	4K	37	30	3	3.4	29	40.2	6.5	36.6
EBG	5K	54	45	4	4.4	44	47.5	8.0	42.1

How to Order



Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.