



SP13 Connector Male Plug and Female Rear Nut
Socket One Pair - 3 Pin

Part Number:

SP1310-P3+SP1312-S3

Basic Information

Connection Type	Docking Type
Contacts	3 Pin
Coupling	Threaded Coupling
Orientation	Straight
Termination	Solder

Material Specification

Contact Material	Brass with Gold Plating
Insert Material	PPS
Shell Material	PA66
Wire Gauge	≅ 2/14(mm ² /AWG)

Electrical Specification

Contact Resistance	2 MΩ
Rated Current	10A
Rated Voltage	250V
Test Voltage	1500V(1min)

Environmental Specification

Ingress Protection	IP68
Operating Temperature	-40°C ~ + 85°C


Mechanical Specification

Mechanical Operation	500 Mating Cycles
----------------------	-------------------

Contact Layout

芯数 Number of contact	2	3	4	5	6	7	9
公端绝缘体正面图 Male contact face view							

Size



How to Order

SP1310 / P	SP1310 / S	电缆外径 Cable outer diameter range
插针 Male contact	插孔 Female contact	I: 4-6.5mm(不标), II: 5-8mm
		芯数 Number of contact

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.