



SP21 Connector Male Rear Nut Socket and Female Plug - 5 B

Part Number:

SP2112-P5B+SP2110-S5B

Basic Information

Connection Type	Docking Type
Contacts	5 B
Coupling	Threaded Coupling
Orientation	Straight
Termination	Crimp, Screw, Solder

Material Specification

Contact Material	Brass with Gold Plating
Insert Material	PPS
Shell Material	PA66

Electrical Specification

Contact Resistance	1 MΩ/5 MΩ
Rated Current	30A/5A
Rated Voltage	250V
Test Voltage	1500V(1min)

Environmental Specification

Ingress Protection	IP68
Operating Temperature	-40°C ~ + 85°C

Mechanical Specification

Mechanical Operation	500 Mating Cycles
----------------------	-------------------

芯数 Number of contact	2	3	4	5	5B	5C	6	6B	7	8	9	12	15
公端绝缘体正面图 Male contact face view													

SP2110/P—9 SP2110/S—9

插针 Male contact 电缆外径 Cable outer diameter range
插孔 Female contact I: 4.5-7mm, II: 7-12mm (不标) III: 5-9mm
芯数 Number of contact

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.