



SP2115/S14 Waterproof Socket Rear-nut Mount 4 Hole Flange Solder

Part Number:

SP2115-S14



Basic Information

Connector Type	SP2115
Contact Termination	Solder
Contact Type	Female Pin
Fastening Type	Threaded
Mounting Feature	4 Hole Flange
Mounting Type	Panel Mount
Number of Positions	14 Pin
Orientation	Straight
Shell Size	M21

Material Specification

Contact Finish	Gold Plating
Contact Material	Copper Alloy
Insulation Material	PPS
Shell Material	Nylon

Rated Current	5A
Rated Voltage	400V

Ingress Protection	IP68
Operating Temperature	-40°C ~ + 85°C

Shielding	Unshielded
1. 10^{-1} to 10^{-2} Sv 2. 10^{-2} to 10^{-3} Sv 3. 10^{-3} to 10^{-4} Sv 4. 10^{-4} to 10^{-5} Sv 5. 10^{-5} to 10^{-6} Sv 6. 10^{-6} to 10^{-7} Sv 7. 10^{-7} to 10^{-8} Sv 8. 10^{-8} to 10^{-9} Sv 9. 10^{-9} to 10^{-10} Sv 10. 10^{-10} to 10^{-11} Sv 11. 10^{-11} to 10^{-12} Sv 12. 10^{-12} to 10^{-13} Sv 13. 10^{-13} to 10^{-14} Sv 14. 10^{-14} to 10^{-15} Sv 15. 10^{-15} to 10^{-16} Sv 16. 10^{-16} to 10^{-17} Sv 17. 10^{-17} to 10^{-18} Sv 18. 10^{-18} to 10^{-19} Sv 19. 10^{-19} to 10^{-20} Sv 20. 10^{-20} to 10^{-21} Sv 21. 10^{-21} to 10^{-22} Sv 22. 10^{-22} to 10^{-23} Sv 23. 10^{-23} to 10^{-24} Sv 24. 10^{-24} to 10^{-25} Sv 25. 10^{-25} to 10^{-26} Sv 26. 10^{-26} to 10^{-27} Sv 27. 10^{-27} to 10^{-28} Sv 28. 10^{-28} to 10^{-29} Sv 29. 10^{-29} to 10^{-30} Sv 30. 10^{-30} to 10^{-31} Sv 31. 10^{-31} to 10^{-32} Sv 32. 10^{-32} to 10^{-33} Sv 33. 10^{-33} to 10^{-34} Sv 34. 10^{-34} to 10^{-35} Sv 35. 10^{-35} to 10^{-36} Sv 36. 10^{-36} to 10^{-37} Sv 37. 10^{-37} to 10^{-38} Sv 38. 10^{-38} to 10^{-39} Sv 39. 10^{-39} to 10^{-40} Sv 40. 10^{-40} to 10^{-41} Sv 41. 10^{-41} to 10^{-42} Sv 42. 10^{-42} to 10^{-43} Sv 43. 10^{-43} to 10^{-44} Sv 44. 10^{-44} to 10^{-45} Sv 45. 10^{-45} to 10^{-46} Sv 46. 10^{-46} to 10^{-47} Sv 47. 10^{-47} to 10^{-48} Sv 48. 10^{-48} to 10^{-49} Sv 49. 10^{-49} to 10^{-50} Sv 50. 10^{-50} to 10^{-51} Sv 51. 10^{-51} to 10^{-52} Sv 52. 10^{-52} to 10^{-53} Sv 53. 10^{-53} to 10^{-54} Sv 54. 10^{-54} to 10^{-55} Sv 55. 10^{-55} to 10^{-56} Sv 56. 10^{-56} to 10^{-57} Sv 57. 10^{-57} to 10^{-58} Sv 58. 10^{-58} to 10^{-59} Sv 59. 10^{-59} to 10^{-60} Sv 60. 10^{-60} to 10^{-61} Sv 61. 10^{-61} to 10^{-62} Sv 62. 10^{-62} to 10^{-63} Sv 63. 10^{-63} to 10^{-64} Sv 64. 10^{-64} to 10^{-65} Sv 65. 10^{-65} to 10^{-66} Sv 66. 10^{-66} to 10^{-67} Sv 67. 10^{-67} to 10^{-68} Sv 68. 10^{-68} to 10^{-69} Sv 69. 10^{-69} to 10^{-70} Sv 70. 10^{-70} to 10^{-71} Sv 71. 10^{-71} to 10^{-72} Sv 72. 10^{-72} to 10^{-73} Sv 73. 10^{-73} to 10^{-74} Sv 74. 10^{-74} to 10^{-75} Sv 75. 10^{-75} to 10^{-76} Sv 76. 10^{-76} to 10^{-77} Sv 77. 10^{-77} to 10^{-78} Sv 78. 10^{-78} to 10^{-79} Sv 79. 10^{-79} to 10^{-80} Sv 80. 10^{-80} to 10^{-81} Sv 81. 10^{-81} to 10^{-82} Sv 82. 10^{-82} to 10^{-83} Sv 83. 10^{-83} to 10^{-84} Sv 84. 10^{-84} to 10^{-85} Sv 85. 10^{-85} to 10^{-86} Sv 86. 10^{-86} to 10^{-87} Sv 87. 10^{-87} to 10^{-88} Sv 88. 10^{-88} to 10^{-89} Sv 89. 10^{-89} to 10^{-90} Sv 90. 10^{-90} to 10^{-91} Sv 91. 10^{-91} to 10^{-92} Sv 92. 10^{-92} to 10^{-93} Sv 93. 10^{-93} to 10^{-94} Sv 94. 10^{-94} to 10^{-95} Sv 95. 10^{-95} to 10^{-96} Sv 96. 10^{-96} to 10^{-97} Sv 97. 10^{-97} to 10^{-98} Sv 98. 10^{-98} to 10^{-99} Sv 99. 10^{-99} to 10^{-100} Sv 100. 10^{-100} to 10^{-101} Sv 101. 10^{-101} to 10^{-102} Sv 102. 10^{-102} to 10^{-103} Sv 103. 10^{-103} to 10^{-104} Sv 104. 10^{-104} to 10^{-105} Sv 105. 10^{-105} to 10^{-106} Sv 106. 10^{-106} to 10^{-107} Sv 107. 10^{-107} to 10^{-108} Sv 108. 10^{-108} to 10^{-109} Sv 109. 10^{-109} to 10^{-110} Sv 110. 10^{-110} to 10^{-111} Sv 111. 10^{-111} to 10^{-112} Sv 112. 10^{-112} to 10^{-113} Sv 113. 10^{-113} to 10^{-114} Sv 114. 10^{-114} to 10^{-115} Sv 115. 10^{-115} to 10^{-116} Sv 116. 10^{-116} to 10^{-117} Sv 117. 10^{-117} to 10^{-118} Sv 118. 10^{-118} to 10^{-119} Sv 119. 10^{-119} to 10^{-120} Sv 120. 10^{-120} to 10^{-121} Sv 121. 10^{-121} to 10^{-122} Sv 122. $10^{-122}</$	

SP2110/P—9 SP2110/S—9

插针 Male contact 电缆直径 Cable outer diameter range
插孔 Female contact I: 4.5~7mm, II: 7~12mm (不标) III: 5~9mm
芯数 Number of contact

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.