



Y50X-1412TK6-B Bayonet Stainless Steel 12 Pin Female Plug with Spring-loaded Tail Clip

Part Number:

Y50X-1412TK6-B

Basic Information

Color	Silver
Connector Type	Plug
Contact Termination	Solder
Contact Type	Female Pin
Fastening Type	Bayonet
Mounting Type	Cable Mount
Number of Positions	12 Pin
Orientation	Straight
Shell Size	14

Material Specification

Contact Finish	Gold Plating
Contact Material	Copper Alloy
Insulation Material	Thermosetting Plastics
Shell Finish	Stainless Steel Passivation
Shell Material	Aluminum Alloy


Environmental Specification

Ingress Protection	IP65
Operating Temperature	-55°C~+125°C

Electrical Specification

Rated Current	5A
Rated Voltage	500V

Contact Layout



Size

【T插头】

壳体号	ΦA	L	M
08	20.5	27	M14×1
0807, 0810	20.5	23.2	M14×1
10	23	27	M18×1
1010, 1013	23	23.2	M18×1
12	26.5	27	M20×1
14	30	27	M24×1
16	33	27	M27×1
18	36	27	M29×1
20	39	27	M33×1
22	42	27	M36×1.5
24	45.5	27	M39×1.5
32	49.5	27.5	M42×1.5

How to Order

Part number

	Y50	X	12	-10	T	J	2	III	H	S	L
Basic series											
Type		X = Solder and hermetic by adhesive P = Solder shielding and hermetic by adhesive A = PCB, solder and hermetic by adhesive C = Hermetic by adhesive without magnetism									
Shell size			08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 32								
Number of contact			2 - 61								
Type of connector					T = Plug Z = Receptacle						
Type of contact					J = Pin K = Socket SJ = Thru bulkhead Pin SK = Thru bulkhead Socket						
Type of plug and receptacle (See below datasheet I)											
Orientation					Omit = N N, W, X, Y, Z (See below)						
Finish					P1 = Electroless nickel plating P2 = Bright nickel plating P3 = Half bright nickel plating H1 = Conductive black L2 = Olive drab cadmium plating H = Black anodized L = Olive drab anodized L1 = Olive drab matte L3 = White anodized						
Material of shell					S = Cooper-alloy B = Stainless steel passivated Omit = Aluminium-alloy						
Length											

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.