



GX16 RP Reverse Plug Connector

Part No.:

GX16-A-2-P



Basic Information	
Part No.	GX16-A-6-P, GX16-A-7-P, GX16-A-8-P, GX16-A-9-P, GX16-A-10-P, GX16-A-3-P, GX16-A-4-P, GX16-A-5-P
Series	GX16
Connection Type	Cable Plug
Orientation	Straight
Contacts	2 Pin, 3 Pin, 4 Pin, 5 Pin, 6 Pin, 7 Pin, 8 Pin, 9 Pin, 10 Pin
Coupling	Threaded Coupling
Gender	Male
Product Type	Panel Mount
Termination	Solder
Shell Material	High Grade Copper Zinc Alloy, Brass Nut
Color	White, Silver, Gold, Black, Blue, OEM
Contact Material	High Grade Copper(Silverplated/Gold)

material_specification	
Insert Material	Bakelite
Wire Gauge	16-24 AWG

Mechanical Specifications

Mechanical Operation	>500 Mating Cycles
Acceleration	100m/s Square

Environmental Specification


Vibration Frequency	10~100Hz
Operating Temperature	-25°C ~ + 85°C

Contact Layout

2 Pin	3 Pin	4 Pin	5 Pin	6 Pin	7 Pin	8 Pin	9 Pin	10 Pin
								

How to Order

Order P/N



Note:

- A: Straight Plug
- B: Panel Mount Socket
- K: Docking Cable Plug
- D: Angled Plug
- E: 3 Hole Circular Flange
- F: Bulkhead
- H: 4 Hole Square Flange

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.