



Feed Through Junction Blocks 60A Outer Screw(M6)  
Red

Part Number:

**RHT-FM6-2034-R**

**Basic Information**

Body Style	Square
Color	Red

**Material Specification**

Contact Material	Aluminum
Flammability	UL94 V-0
Insulation Material	PBT

**Mechanical Specification**

Contact Termination	Screw
Docking Method	Thread
Insertion Times	> 500
Mounting Feature	Bulkhead
Mounting Type	Panel Mount
Termination Thread	M6

**Electrical Specification**

Dielectric Strength	3000V
Rated Current	60A
Rated Voltage	250V

**Environmental Specification**

Operating Temperature	-40°C to +125°C
-----------------------	-----------------

## Size



## How to Order

1. Specify the upper and lower mounting thread specifications.
2. Specify the panel cutout shape.
3. Specify the rated current.
4. Specify whether waterproofing is required.
5. Specify whether a protective cap is needed.
6. Specify the main body color.

### **FOR EXAMPLE:**

The product with an installation end M8 internal thread structure, a two-ear flange mounting base, a 500A rated current, and an insulation protective cover has the part number RHT-FM8-3457-32-500A-C.

## Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.