



ZH127 Series Connector Shell Size 14 10pin Female Plug with Straight Tail Attachment - CHЦ127-10/14PП126-1-B

Part Number:

**ZH127-10\_14P12Q-1-B**



### Basic Information

Connector Type	Plug
Contact Type	Female
Mounting Type	Cable Mount
Fastening Type	Bayonet Connection
Shell Size	14
Number of Positions	10
Orientation	Straight

### Compatible Part Numbers

Russian P/N	CHЦ127-10/14PП126-1-B
-------------	-----------------------

### Material Specification

Contact Material	Gold/Silver plating
Shell Material	Aluminum alloy

**Environmental Specification**


Vibration	1-5000Hz 20g
Operating Temperature	-60 °C ~ +105 °C


**Electrical Specification**

Insulating Materials	Bakelite
Insulation Impedance	$\geq 5000M\Omega$
Contact Resistance	$\leq 5m\Omega$
Operating Current	3A
Operating Voltage	250V

**Mechanical Specification**

Mechanical and Working Life	500 cycles
Contact Dia.	$\varnothing 1.0 \text{ mm}$

**Contact Layout**


**Size**


Shell size	D	d	Lmax
10	20	6	26.5
12	21	8	28.5
14	24	9	31.5
18	27	11	34.5
22	31	13	35.5
27	36	16	39.5

**How to Order**
**CHINESE**

ZH127-	4	/10	B(P)	1 (2)	1 (2)	Z	1	B
Series								
Contacts:1/2/4/6/7/10/14/19/30/32/50/76/102								
Shell Size: 10/12/14/18/22/27								
Contacts gender: B(Male) P(Female)								
Connection Type (Socket Only) 1: Solder 2: PCB								
1: Gold Plating 2: Silver Plating								
W-Plug with angled tail attachment Q-Plug with straight tail attachment Z-Four-hole flange socket Y-Plug with short sleeve tail attachment								
Positioning Direction: 1-20								
All-climate Version								

**Disclaimer**

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.